



I.D. Booth Inc. & Booth Electric Supply

Now stocking UeI Test Instruments



IDBOOTHKIT Complete Gas Service Kit

- Includes DL579, CD100, EM720SPKIT, PDT655, COA2, C163, AC550



522KIT Oil Burner & Boiler Install Kit

- Includes C161, DL579, CD100A, EM720SPKIT, PDT655, SPT1, AC550



511KIT Heat Pump Install Kit

- Includes DL579, EM720SPKIT, RLD15B, HUB8, AC550



HUB8 Wireless Refrigeration System Analyzer w/ Vacuum Gauge

- View all indoor and outdoor AC/R system parameters from one location



C163KIT Residential/Commercial Combustion Analyzer Kit w/ Pressure/Printer

- Backed by UeI Service+
- Up to 10-Year warranty with annual recertification



C161 Residential Combustion Analyzer

- Backed by UeI Service+
- Up to 10-Year warranty with annual recertification



COA2 Portable Carbon Monoxide Detector w/ Wireless Capabilities

- Reads up to 999ppm CO
- Wireless or stand-alone



DL579 600A True-RMS Dual Display HVAC/R Clamp Meter w/ Temperature & Capacitance



DL369 Dual Display Clamp Meter

- 400A AC/DC, 750V AC/1000V DC
- Dual display



DM505 1000V Digital Multimeter

- 10A AC/DC, 1000V AC/DC
- μ A/mA



EM720 Hi-Res Differential Manometer

- Temperature compensated
- +80 lnWC
- Measures in 11 scales



CD100A Combustible Gas Leak Detector

- < 50 ppm methane sensitivity



RLD15B Refrigerant Leak Detector

- Digital numeric leak size indicator
- 3 Sensitivity levels





I.D. Booth Inc. & Booth Electric Supply

Now stocking U*Ei* Test Instruments



DMG150
*Digital Vacuum Gauge
w/ Contamination Sensor*

- Range 0 to 15,000 microns
- Maximum over pressure 700 psi



DTHA2
*Wireless Airflow/
Humidity/ Temperature
Meter*

- iOS® and Android™ compatible
- Airflow 217 to 3937 ft/sec



DTH35
*Digital Pocket
Psychrometer
w/ Temperature/
Relative Humidity/
Enthalpy*



DT720
*Dual Input
Temperature Tester*

- 2 Inputs
- Differential T1-T2



INF195C
*12:1 Infrared
Thermometer w/
K-Type Input*

- Circular laser defines target
- Differential temperature



PDT650
*Back Probe Test
Lead Kit*

- Tip measures in any position
- Min/Max/Record



PDT550
*Digital Pocket
Thermometer NSF*

- Min/Max/Record
- Auto power off
- Built-in magnetic mount



ATTPC3
*K-Type Pipe Clamp
Probe (grip style)*

- Temperature range:
- -40° to 500°F (-40° to 260°C)



ATLBPK
*Back Probe
Test Lead Kit*



SPT1
*Smoke Pump
Test Kit*

- To measure and test combustion smoke in your flue



17631
*Particle Filter
(C Series Analyzers)*

- Works with C20, C30, C50, C75, C091, C095, C85, C125, C127, C155, C157, C255, C257, C165