






	Description	SKU #	Color/Finish	List Price
	<p>Aspirations™ Single-Handle Pull-Out Bathroom Faucet 1.2 gpm/ 4.5 L/min With Lever Handle</p> <ul style="list-style-type: none"> • Washerless ceramic disc valve cartridge • Water-conserving 1.2 gpm/4.5 L/min pressure-compensating aerator • Metal push pop-up drain and lever handle • Lead Free • Braided flexible hoses with 3/8" (10 mm) compression connections • Pull-Out Wand 	 7061121.002	Polished Chrome	337
		7061121.243	Matte Black	472
		7061121.295	Brushed Nickel	472
	<p>Aspirations™ Single-Handle Petite Bathroom Faucet 1.2 gpm/ 4.5 L/min With Lever Handle</p> <ul style="list-style-type: none"> • Washerless ceramic disc valve cartridge • Water-conserving 1.2 gpm/4.5 L/min pressure-compensating aerator • Metal push pop-up drain and lever handle • Lead Free • Braided flexible hoses with 3/8" (10 mm) compression connections 	 7061131.002	Polished Chrome	264
		7061131.243	Matte Black	370
		7061131.295	Brushed Nickel	370
	<p>Aspirations™ Single Handle Wall-Mount Faucet 1.2 gpm/4.5 L/min With Lever Handle</p> <ul style="list-style-type: none"> • Metal Construction • 35mm washerless ceramic disc valve cartridge • Water-conserving 1.2 gpm/4.5 L/min pressure-compensating aerator • Lead Free • Brass grid drain 	 7061461.002	Polished Chrome	448
		7061461.243	Matte Black	628
		7061461.295	Brushed Nickel	628
	<p>Aspirations™ 4-Hole 2-Handle Deck Mount Roman Tub Faucet With Lever Handles and Personal Shower</p> <ul style="list-style-type: none"> • Brass construction • Metal lever handles • Personal shower with 1.8 gpm/6.8 L/min maximum flow • Personal showers feature 5' (152 cm) long hose • For use with Flash® bathtub faucet rough-in valve R910 • Valve sold separately 	 T061901.002	Polished Chrome	512
		T061901.243	Matte Black	717
		T061901.295	Brushed Nickel	717
	<p>Flash® Bathtub Filler Rough-In Valve With Personal Shower</p> <ul style="list-style-type: none"> • Brass construction and washerless ¼-turn ceramic disc valves cartridge • ½" (13 mm) copper inlets • Connections to spout can be made via flexible hoses (provided) or ½" (13 mm) copper sweat connections • 14 gpm/59.2 L/min maximum flow rate at 40 psi • 8"-16" (203-406 mm) flexible installation • Adjustable rough-in: 2-½" (64 mm) maximum deck thickness • Includes hand shower rough-in 	R910	No Finish	322

