






	Description	SKU #	Color/Finish	List Price
	<p>Flash® Shower Rough-In Valve With Universal Inlets/Outlets</p> <ul style="list-style-type: none"> • ½" (13 mm) male NPT/Sweat inlets/outlets accept ½" copper, ½" iron pipe, PEX or CPVC adapters • Cast DZR brass valve body • Flow rate: 5.1 gpm @ 45 psi* • Back-to-back capability • Includes flush plug with stainless steel ring • Cartridge ships with trim • For use with TU series pressure balance bath/shower trim kits 	RU101	No Finish	72
	<p>Flash® Shower Rough-In Valve With Universal Inlets/Outlets With Screwdriver Stops</p> <ul style="list-style-type: none"> • ½" (13 mm) male NPT/Sweat inlets/outlets accept ½" copper, ½" iron pipe, PEX or CPVC adapters • Cast DZR brass valve body • Flow rate: 5.1 gpm @ 45 psi* • Back-to-back capability • Includes flush plug with stainless steel ring • Includes screwdriver stops for easy servicing at the valve • For use with TU series pressure balance bath/shower trim kits 	RU101SS	No Finish	103
	<p>Flash® Shower Rough-In Valve With Stub-Outs</p> <ul style="list-style-type: none"> • ½" (13 mm) Stub-out inlets/outlets accept ½" press-connect fittings • Cast DZR brass valve body • Flow rate: 5.1 gpm @ 45 psi* • Back-to-back capability • Includes flush plug with stainless steel ring • Cartridge ships with trim • For use with TU series pressure balance bath/shower trim kits 	RU102	No Finish	72
	<p>Flash® Shower Rough-In Valve With Stub-Outs With Screwdriver Stops</p> <ul style="list-style-type: none"> • ½" (13 mm) Stub-out inlets/outlets accept ½" press-connect fittings • Cast DZR brass valve body • Flow rate: 5.1 gpm @ 45 psi* • Back-to-back capability • Includes flush plug with stainless steel ring • Includes screwdriver stops for easy servicing at the valve • Cartridge ships with trim • For use with TU series pressure balance bath/shower trim kits 	RU102SS	No Finish	103
	<p>Flash® Shower Rough-In Valve With PEX Inlets/Universal Outlets for Crimp Ring System</p> <ul style="list-style-type: none"> • ½" (3 mm) PEX crimp inlets/Universal outlets (ASTM F1807) • Cast DZR brass valve body • Flow rate: 5.1 gpm @ 45 psi* • Back-to-back capability • Includes flush plug with stainless steel ring • Cartridge ships with trim • For use with TU series pressure balance bath/shower trim kits 	RU107	No Finish	72

*When combined with Double Ceramic pressure balance cartridge.