




	Description	SKU #	Color/Finish	List Price
	<p>Flash® Shower Rough-In Valve With PEX Inlets/Universal Outlets With Screwdriver Stops for Crimp Ring System</p> <ul style="list-style-type: none"> • ½" (13 mm) PEX crimp inlets/Universal outlets (ASTM F1807) • Cast DZR brass valve body • Flow rate: 5.1 gpm @ 45 psi* • Back-to-back capability • Includes flush plug with stainless steel ring • Includes screwdriver stops for easy servicing at the valve • Cartridge ships with trim • For use with TU series pressure balance bath/shower trim kits 	RU107SS	No Finish	103
	<p>Flash® Shower Rough-In Valve With PEX Inlet Elbows/Universal Outlets for Crimp Ring System</p> <ul style="list-style-type: none"> • ½" (13 mm) PEX crimp elbow inlets/Universal outlets (ASTM F1807) • Cast DZR brass valve body • Flow rate: 5.1 gpm @ 45 psi* • Back-to-back capability • Includes flush plug with stainless steel ring • Cartridge ships with trim • For use with TU series pressure balance bath/shower trim kits 	RU107E	No Finish	95
	<p>Flash® Shower Rough-In Valve With PEX Inlet Elbows/Universal Outlets With Screwdriver Stops for Crimp Ring System</p> <ul style="list-style-type: none"> • ½" (13 mm) PEX crimp elbow inlets/Universal outlets (ASTM F1807) • Cast DZR brass valve body • Flow rate: 5.1 gpm @ 45 psi* • Back-to-back capability • Includes flush plug with stainless steel ring • Includes screwdriver stops for easy servicing at the valve • Cartridge ships with trim • For use with TU series pressure balance bath/shower trim kits 	RU107ESS	No Finish	125
	<p>Flash® Shower Rough-In Valve With PEX Inlets/Universal Outlets for Cold Expansion System</p> <ul style="list-style-type: none"> • ½" (13 mm) PEX cold expansion inlets/Universal outlets (ASTM F1960) • Cast DZR brass valve body • Flow rate: 5.1 gpm @ 45 psi* • Back-to-back capability • Includes flush plug with stainless steel ring • Cartridge ships with trim • For use with TU series pressure balance bath/shower trim kits 	RU108	No Finish	72
	<p>Flash® Shower Rough-In Valve With PEX Inlets/Universal Outlets With Screwdriver Stops for Cold Expansion System</p> <ul style="list-style-type: none"> • ½" (13 mm) PEX cold expansion inlets/Universal outlets (ASTM F1960) • Cast DZR brass valve body • Flow rate: 5.1 gpm @ 45 psi* • Back-to-back capability • Includes flush plug with stainless steel ring • Includes screwdriver stops for easy servicing at the valve • For use with TU series pressure balance bath/shower trim kits 	RU108SS	No Finish	103

*When combined with Double Ceramic pressure balance cartridge.